





HCRH0630 TYPE

TYPE

HCRH 0630



A: 6.6 ± 0.3
B: 6.2 ± 0.3
C: 3.0 MAX.
D: 1.5 REF

DIMENSION

SPECIFICATION

| ITEM | L | DCR | IDC |
|----------|-------------------|------------------|---------|
| HCRH0630 | (μH) | MAX.(Ω) | MAX.(A) |
| 100M | 10 \pm 20% | 0.150 | 1.10 |
| 120M | 12 \pm 20% | 0.200 | 1.00 |
| 150M | 15 \pm 20% | 0.230 | 0.90 |
| 180M | 18 \pm 20% | 0.270 | 0.80 |
| 220M | 22 \pm 20% | 0.340 | 0.74 |
| 270M | 27 \pm 20% | 0.380 | 0.66 |
| 330M | 33 \pm 20% | 0.450 | 0.59 |
| 390M | 39 \pm 20% | 0.490 | 0.54 |
| 470M | 47 \pm 20% | 0.690 | 0.50 |
| 560M | 56 \pm 20% | 0.780 | 0.46 |
| 680M | 68 \pm 20% | 1.070 | 0.42 |
| 820M | 82 \pm 20% | 1.210 | 0.38 |
| 101M | 100 \pm 20% | 1.390 | 0.34 |
| 121M | 120 \pm 20% | 1.900 | 0.31 |
| 151M | 150 \pm 20% | 2.180 | 0.28 |
| 181M | 180 \pm 20% | 2.770 | 0.26 |
| 221M | 220 \pm 20% | 3.120 | 0.23 |

J: $\pm 5\%$, K: $\pm 10\%$, M: $\pm 20\%$

* Hong can design any part to your requirements with different inductance.

* All parameters as this content presented are subject to final specifications both sides confirmed.