


HNR4010S Series

TYPE

HNR4010S



DIMENSION



A:4.0±0.2
B:4.0±0.2
C:1.0Max
D:3.3±0.2
E:0.95±0.2
F:2.1±0.2

SPECIFICATION

Part Number	Inductance @100kHz,1V	DC Resistance (± 20%)	Min.		Heat Rating Current
			Self-resonant Frequency	Saturation Current	
Units Symbol	μH L	Ω DCR	MHz S.R.F	A Isat	A Irms
HNR4010S1R0NT	1.0 ± 30%	0.056	116	2.00	1.90
HNR4010S1R5NT	1.5 ± 30%	0.070	94	1.68	1.70
HNR4010S2R2MT	2.2 ± 20%	0.085	73	1.20	1.50
HNR4010S3R3MT	3.3 ± 20%	0.100	58	1.10	1.40
HNR4010S4R7MT	4.7 ± 20%	0.140	47	0.95	1.20
HNR4010S6R8MT	6.8 ± 20%	0.200	38	0.80	1.00
HNR4010S100MT	10 ± 20%	0.300	31	0.62	0.75
HNR4010S150MT	15 ± 20%	0.430	24	0.54	0.60
HNR4010S220MT	22 ± 20%	0.570	19	0.45	0.50

* Hong can design any part to your requirements with different inductance.

* All parameters as this content presented are subject to final specifications both sides confirmed.