


HPC0302 TYPE

TYPE

DIMENSION

HPC 0302: 1.5 μ H ~ 150 μ H



A: 3.5 \pm 0.3

B: 3.1 \pm 0.3

C: 2.1 \pm 0.3

D: 1.2 \pm 0.3

SPECIFICATION

ITEM	L	DCR	IDC
HPC0302	(μ H)	MAX. (Ω)	MAX. (A)
1R5M	1.5 \pm 20%	0.06	2.00
2R2M	2.2 \pm 20%	0.09	1.60
3R3M	3.3 \pm 20%	0.10	1.50
4R7M	4.7 \pm 20%	0.20	1.40
6R8M	6.8 \pm 20%	0.30	1.00
8R2M	8.2 \pm 20%	0.32	1.00
100M	10 \pm 20%	0.35	1.00
120M	12 \pm 20%	0.40	0.90
150M	15 \pm 20%	0.60	0.60
180M	18 \pm 20%	0.70	0.60
220M	22 \pm 20%	1.00	0.50
270M	27 \pm 20%	1.10	0.45
330M	33 \pm 20%	1.30	0.40
390M	39 \pm 20%	1.50	0.35
470M	47 \pm 20%	2.00	0.35
680M	68 \pm 20%	2.20	0.30
820M	82 \pm 20%	2.80	0.25
101M	100 \pm 20%	3.20	0.20
121M	120 \pm 20%	4.00	0.18
151M	150 \pm 20%	4.30	0.15

M: \pm 20%

* Hong can design any part to your requirements with different inductance.

* All parameters as this content presented are subject to final specifications both sides confirmed.